

# Senseair S8 2%



## A very small, versatile and mass-producible CO<sub>2</sub> sensor module

More than 30 years experience of research and development within the field of infrared gas sensing has now brought us the smallest CO<sub>2</sub> sensor, with NDIR-technology in the world – Senseair S8 2%. The new sensor has excellent performance such as high accuracy and low power consumption.

Senseair S8 2% is designed for high volume production with full traceability by sensor serial number on all manufacturing processes and key components. Every sensor is individually calibrated and is provided with UART digital interface. The sensor is maintenance-free and has an estimated life time of more than 15 years.

Senseair S8 2% is a module that is designed for simple integration into products. Senseair S8 2% can be used in a wide range of applications such as in ventilation control to improve energy savings and to ensure a good indoor climate. Other fields of use are personal safety and measurements to increase process yield and to increase economic value in bio-related processes.

## Standard specification

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Measured gas                      | Carbon dioxide (CO <sub>2</sub> )     |
| Operating principle               | Non-dispersive infrared (NDIR)        |
| Measurement range CO <sub>2</sub> | 0.04–2%vol                            |
| Accuracy CO <sub>2</sub>          | ±200ppm ±3% of reading <sup>1,2</sup> |
| Maintenance                       | No maintenance required               |
| Life expectancy                   | > 15 years                            |
| Power supply                      | 4.5–5.25VDC                           |
| Operation temperature range       | 0–50 °C                               |
| Communication                     | UART (Modbus)                         |
| Dimensions [mm]                   | 33.9 x 19.8 x 8.7                     |
| Power consumption                 | 300mA peak<br>30mA average            |
| Response time                     | 2 minutes by 90%                      |

## Key benefits

- Miniature size
- Individually calibrated
- Maintenance-free
- Long term stability
- Low power consumption

Note 1: In normal IAQ applications. Accuracy is defined after minimum three (3) ABC periods of continuous operation with ABC on.

Note 2: Accuracy is specified over operating temperature range. Specification is referenced to certified calibration mixtures. Uncertainty of calibration gas mixtures (±1% currently) is to be added to the specified accuracy for absolute measurements.

